

CAT LINE CAT 5e R / 6A R / 7A R

할로겐 프리 산업용 이더넷 케이블 철도 기술 용



Marking for CATLine CAT 5e R 15674421:

SAB BRÖCKSKES · D-VIERSEN · CATLine Cat.5e R 4x2x24AWG 1567-4421 CE

Construction:	CATLine CAT 5e R <i>flexible</i>		CATLine CAT 6A R <i>flexible</i>	CATLine CAT 7A R <i>flexible</i>
Dimension:	2 x 2 x 24 AWG 2 x 2 x 22 AWG	4 x 2 x 24 AWG	4 x 2 x 26 AWG	
Conductor:	bare copper strands, fine wires			
Insulation:	PE			
Colour code:	blue, yellow, white, orange	white-blue/blue, white-orange/orange, white-green/green, white-brown/brown		
Stranding:	star quad	twisted to pairs		twisted to pairs with alu foil
Wrapping:	foil			
Screen:	alu foil and tinned copper braiding			
Sheath material:	special SABIX®			
Sheath colour:	green (similar RAL 6018)			

Technical data:	CATLine CAT 5e R <i>flexible</i>		CATLine CAT 6A R <i>flexible</i>	CATLine CAT 7A R <i>flexible</i>
Item number:	1567-9002 1567-9004	1567-4421	1667-4621	1767-4621
Peak operating voltage:	max. 90 V			
Testing voltage:	core/core 1500 V - core/screen 1200 V			
Temperature range VDE fixed laying: flexible application:	- 40°C / + 70°C - 30°C / + 70°C			
Min. bending radius fixed laying: flexible application:	5 x d 12 x d			
Characteristic impedance:	100Ω ± 5Ω, accomplishes the electrical and transmission requirements with high frequency with reference to EN 50288-2-2 / CAT 5	100Ω ± 10Ω, accomplishes the electrical and transmission requirements with high frequency with reference to EN 50288-2-2 / CAT 5	100Ω ± 10Ω, accomplishes the electrical and transmission requirements with high frequency with reference to EN 50288-10-2 / CAT 6A	100Ω ± 10Ω, accomplishes the electrical and transmission requirements with high frequency with reference to EN 50288-9-2 / CAT 7A
Halogen-free:	acc. to DIN EN 50306-1 + DIN EN 50264-1. Development of HCl is ≤ 0,5% acc. to DIN EN 50267-2-1. pH-value is ≥ 4,3 acc. to DIN EN 50267-2-2. Conductivity is ≤ 10,0 μS/mm acc. to DIN EN 50267-2-2. Fluoric content ≤ 0,1% acc. to DIN EN 60684-2			
Fire performance:	No flame propagation acc. to DIN EN 60332-3-25 + DIN EN 50305 section 9.1.1 + 9.1.2. Flame retardant and self-extinguishing acc. to DIN EN 60332-1-2			
Smoke density:	acc. to DIN EN 61034			
Toxicity:	acc. to DIN EN 50305			
Flexibility:	good			
Absence of harmful substances:	acc. to RoHS directive of the European Union			



Outstanding features:

- halogen-free
- no flame propagation
- flame retardant and self-extinguishing
- fulfils fire protection requirements R15 (EL1A) acc. to DIN EN 45545-2 for hazard levels HL1-3
- EAC approval

item no.	type	no. of cores	cross section AWG	core-ø max. mm	outer-ø ± 5% mm	copper figure kg/km	cable weight ≈kg/km
15679002	CATLine CAT 5e R	4	24	max. 1,30	5,2 ± 5%	22,7	41
15679004	CATLine CAT 5e R	4	22	max. 1,60	5,9 ± 5%	29,1	52
15674421	CATLine CAT 5e R	8	24	max. 1,30	8,0 ± 10%	41,2	70
16674621	CATLine CAT 6A R	8	26	max. 1,05	6,8 ± 10%	31,9	55
17674621	CATLine CAT 7A R	8	26	max. 1,60	7,8 ± 10%	38,5	75

Other dimensions and colours are possible on request.