


Servo Motor Cables

SL 834 C

low capacity PUR motor connection cable with overall copper screen 0.6/1 kV



20235 80°C CSA AWM I/II A/B 80°C 1000V FT1 FT2 CE



marking example:

SAB BBRÖCKSKES · D-VIERSEN · 08340415 4x1,5mm² SL 834 C 16 AWG/4c 1000V 08341604

DESINA AWM Style 20235 80°C CSA AWM I/II A/B 80°C 1000V FT1 FT2 CE

Construction:

Conductor:	bare copper strands acc. to IEC 60228, VDE 0295, class 6
Insulation:	special polymer
Colour code:	black cores with consecutive numbers acc. to EN 50334 + VDE 0293-334 and a green-yellow earth wire
Stranding:	in layers
Wrapping:	non-woven tape
Screen:	tinned copper braiding
Sheath material:	PUR
Sheath colour:	orange (RAL 2003)

Outstanding features:

- » UL recognized, CSA approval
- » low capacity construction
- » very good EMC characteristics
- » halogen-free
- » very high flexibility
- » suitable for cable tracks
- » very good oil resistance
- » very long service life
- » adhesion-free installation
- » PWIS uncritical
(PWIS = paint-wetting impairment substances)
- » flexible at low temperatures
- » DESINA® colours (see page C/4)

Technical data:

Nominal voltage:	U ₀ /U 0.6/1 kV
Voltage UL/CSA:	1000 V
Testing voltage:	core/core 4000 V core/screen 4000 V
Min. bending radius	
fixed laying:	5 x d
flexible application:	10 x d
Temperature range	DIN VDE UL/CSA: up to +80 °C
fixed laying:	-50/+90 °C
flexible application:	-40/+90 °C
Halogen-free:	acc. to IEC 60754-1 + VDE 0482-754-1
Fire performance:	flame retardant and self-extinguishing acc. to IEC 60332-1-2 + VDE 0482-332-1-2, CSA FT1, FT2
Oil resistance:	very good - TMPU acc. to EN 50363-10-2 + VDE 0207-363-10-2
Chem. resistance:	good against acids, alkalines, solvents, hydraulic liquids etc.
Absence of harmful substances:	acc. to RoHS directive of the European Union, see chapter N „Technical data“

low capacity
for your frequency controlled
drives and motors

item no.	no. of cores x cross section n x mm²	AWG	largest single wire ø mm	outer-ø ± 10% mm	copper figure kg/km	cable weight ≈ kg/km
08340415	4 x 1,50	16/4c	0,16	9,0	83,5	126
08340425	4 x 2,50	14/4c	0,16	10,8	142,5	195
08340440	4 x 4,00	12/4c	0,16	12,4	206,5	270
08340460	4 x 6,00	10/4c	0,21	15,4	298,1	398
08340470	4 x 10,00	8/4c	0,21	17,6	494,7	604
08340480	4 x 16,00	6/4c	0,21	22,7	749,7	953
08340490	4 x 25,00	4/4c	0,21	25,6	1119,8	1303
08340495	4 x 35,00	2/4c	0,21	28,9	1532,9	1750
08340496	4 x 50,00	1/4c	0,31	34,5	2144,5	2486

Other dimensions and colours are possible on request.

Note: DESINA® is a registered trademark of the German Machine Tool Builders' Association.